



Report Number: 18-005851

Revision Number:1

Date Order Received: 09/26/2018

For the Account of: Camira Fabrics Ltd.

Meltham Mills

Meltham

Holmfirth, West Yorkshire HD9 4AY

United Kingdom

Client's Identification: ZAP Denim

CERTIFICATE OF TESTING

TEST PERFORMED: Abrasion Resistance of Textile Fabrics (Martindale Abrasion Tester Method) ASTM D4966-12E1

TEST RESULTS

Specimen	Number of Cycles	Rating
1	100,000	No breakage or appreciable wear
2	100,000	No breakage or appreciable wear
3	100,000	No breakage or appreciable wear

INTERPRETATION USED

Option 1 The end point is reached on a woven fabric when two or more yarns have broken or on a knitted fabric, when a hole

appears.

☐ Option 2 The end point is reached when there is a change in shade or appearance that is sufficient to cause a

customer to complain.

NOTES

Test Conditions: 70 ±4°F, 65 ±5% Relative Humidity

Sampling Method: As Received

Abradant Used: Worsted Wool Standard Abradant Fabric

Weight: $12 \pm 0.3 \text{ kPa}$

Foam Backing Used: ☐ No ☒ Yes

Approximate Weight

Of Fabric: 14.1 ounces / square yard

ACCEPTANCE CRITERIA

A.C.T. Standard Acceptance Criteria

General Contract Upholstery

No appreciable breakage or wear after 20,000 cycles

Heavy Duty Upholstery

No appreciable breakage or wear after 40,000 cycles

CONCLUSION Based on the above Results and the A.C.T. Standard, the item tested:

□ Unrated

☐ General Contract Upholstery ☐ Heavy Duty Upholstery

CERTIFICATION I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

Chelsea Rybishi

Authorized Signature Date Order Completed: 10/03/2018

553 76th Street, Byron Center, MI 49315

P: 616-559-6123 E: testlab@applied-textiles.com

Page 1 of 1