
FLAMMABILITY TEST CERTIFICATE – 66862

COMPANY DETAILS: CAMIRA FABRICS LTD
MELTHAM MILLS, MELTHAM
WEST YORSHIRE, HD9 4AY

CONTACT NAME(S): KATY LONGSTAFF
TEL: 01924 481 366
EMAIL: katy.longstaff@camirafabrics.com

DATE RECEIVED: 18/04/2018
DATE TESTED: 23/04/2018
DATE ISSUED: 23/04/2018
PO NUMBER: 61688

SAMPLE DESCRIPTION: 24/7+
COLOUR: HOUR
QUALITY/BATCH REF: 370951
MODEL REF: NOT STATED
COMPOSITION: 50% POLYAMIDE, 33% WOOL, 10% FLAME RETARDANT VISCOSE, 7% VISCOSE
SAMPLE END USE: NOT STATED
MANUFACTURER: NOT STATED
SUPPLIER/BUYER: NOT STATED

SPECIFICATION/REQUIREMENT:

BS 7176:2007+A1:2011 – Specification for the resistance to ignition of upholstered furniture for non-domestic seating by testing composites. (Low Hazard)

TEST METHOD:

BS EN 1021-1:2006 – Furniture – Assessment of the ignitibility of mattresses and upholstered bed bases. Part 1: Ignition source smouldering cigarette.

BS EN 1021-2:2006 – Furniture – Assessment of the ignitibility of mattresses and upholstered bed bases. Part 2: Ignition source match flame equivalent.

PRE-TREATMENT:

The sample was tested as received by the customer as requested by the customer.

CONDITIONING:

The sample was conditioned for 72 hrs in ambient conditions for at least 24 hrs in a specified atmosphere at $23 \pm 2^{\circ}\text{C}$ and $50 \pm 5\%$ r h.

Authorised By:



Zeb Alam
Operations Director

Mark Jones
Quality Manager

Karen Brooks
Managing Director

FLAMMABILITY TEST CERTIFICATE – 66862

TEST RESULTS:

“The Following test results relate only to the ignitibility of the combination of the materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.”

TEST CRITERIA – 1021-1 (CIGARETTE TEST)	INITIAL TEST	REPEAT TEST
FILLING MATERIAL USED:	CMHR 35	CMHR 35
Cigarette ceased smouldering within (Min(s))	21.23	20.38
PROGRESSIVE SMOULDERING CRITERIA (3.1)		
Unsafe escalating combustion (3.1a)	N	N
Smoulders to extremities (3.1b)	N	N
Smoulders through thickness (3.1c)	N	N
Smoulders for more than 1 hr (3.1d)	N	N
Presence of active smouldering on final examination? (3.1e)	N	N
Evidence of melting, charring, dripping?	Melting: <input checked="" type="checkbox"/>	Charring: <input checked="" type="checkbox"/> Dripping: <input type="checkbox"/>
FLAMING CRITERIA (3.2)		
Cover Split?	N	N
Occurrence of flames?	N	N
TEST RESULT	PASS	PASS

TEST CRITERIA – 1021-2 (MATCH TEST)	1 st Test	2 nd Test	3 rd Test
FILLING MATERIAL USED:	CMHR 35	CMHR 35	CMHR 35
Cigarette ceased smouldering within (Min(s))	0.0	0.0	0.0
PROGRESSIVE SMOULDERING CRITERIA (3.1)			
Unsafe escalating combustion (3.1a)	N	N	N
Smoulders to extremities (3.1b)	N	N	N
Smoulders through thickness (3.1c)	N	N	N
Smoulders for more than 1 hr (3.1d)	N	N	N
Evidence of melting, charring, dripping?	Melting: <input checked="" type="checkbox"/>	Charring: <input checked="" type="checkbox"/> Dripping: <input type="checkbox"/>	
FLAMING CRITERIA (3.2)			
Unsafe escalating combustion (3.2a)	N	N	N
Test assembly consumed (3.2b)	N	N	N
Flaming to extremities and thickness (3.2c) (3.2d)	N	N	N
Flaming continued for more than 120 seconds	N	N	N
Cover split?	N	N	N
TEST RESULT	PASS	PASS	PASS

CONCLUSION:

The sample supplied **meets** the test criteria of BS 7176:2007 + A1:2011 (Low Hazard)

END OF REPORT