
FLAMMABILITY TEST CERTIFICATE – 79599

COMPANY DETAILS: CAMIRA FABRICS LTD
MELTHAM MILLS, MELTHAM
WEST YORSHIRE, HD9 4AY

CONTACT NAME(S): LUKE RUSSELL
TEL: 01924 481 368
EMAIL: luke.russell@camirafabrics.com

DATE RECEIVED: 18/12/2019
DATE TESTED: 07/01/2020
DATE ISSUED: 08/01/2020
PO NUMBER: 83A07045

SAMPLE DESCRIPTION: LUCIA I2
COLOUR: D9078M
QUALITY/BATCH REF: 436294
MODEL REF: NOT STATED
COMPOSITION: NOT STATED
SAMPLE END USE: UPHOLSTERY
MANUFACTURER: CAMIRA FABRICS
SUPPLIER/BUYER: NOT STATED

SPECIFICATION/REQUIRMENT:

BS 7176:2007+A1:2011 – Specification for the resistance to ignition of upholstered furniture for non-domestic seating by testing composites. (Low Hazard)

TEST METHOD:

BS EN 1021-1:2006 – Furniture – Assessment of the ignitibility of upholstered furniture. Ignition source smouldering cigarette.

BS EN 1021-2:2006 – Furniture – Assessment of the ignitibility of upholstered furniture. Ignition source match flame equivalent.

PRE-TREATMENT:

The sample was tested as received by the customer.

CONDITIONING:

The sample was conditioned for 72 hrs in ambient conditions for at least 24 hrs in a specified atmosphere at $23 \pm 2^{\circ}\text{C}$ and $50 \pm 5\%$ r h.

Authorised By:



Zeb Alam
Operations Director

Mark Jones
Quality Manager

Karen Brooks
Managing Director

FLAMMABILITY TEST CERTIFICATE – 79599

TEST RESULTS:

“The Following test results relate only to the ignitibility of the combination of the materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.”

TEST CRITERIA – 1021-1 (CIGARETTE TEST)	INITIAL TEST	REPEAT TEST
FILLING MATERIAL USED:	CMHR 35	CMHR 35
Cigarette ceased smouldering within (Min(s))	<60.00	FTS
PROGRESSIVE SMOULDERING CRITERIA (3.1)		
Unsafe escalating combustion (3.1a)	NO	NO
Smoulders to extremities (3.1b)	NO	NO
Smoulders through thickness (3.1c)	NO	NO
Smoulders for more than 1 hr (3.1d)	NO	NO
Presence of active smouldering on final examination? (3.1e)	NO	NO
Evidence of melting, charring, dripping?	Melting: <input checked="" type="checkbox"/>	Charring: <input checked="" type="checkbox"/> Dripping: <input type="checkbox"/>
FLAMING CRITERIA (3.2)		
Cover Split?	YES	YES
Occurrence of flames?	NO	NO
TEST RESULT	PASS	PASS

TEST CRITERIA – 1021-2 (MATCH TEST)	1 st Test	2 nd Test	3 rd Test
FILLING MATERIAL USED:	CMHR 35	CMHR 35	CMHR 35
Flaming Ceased: Min(s) Sec(s)	0.00	0.01	0.00
PROGRESSIVE SMOULDERING CRITERIA (3.1)			
Unsafe escalating combustion (3.1a)	NO	NO	NO
Smoulders to extremities (3.1b)	NO	NO	NO
Smoulders through thickness (3.1c)	NO	NO	NO
Smoulders for more than 1 hr (3.1d)	NO	NO	NO
Evidence of melting, charring, dripping?	Melting: <input checked="" type="checkbox"/>	Charring: <input checked="" type="checkbox"/> Dripping: <input type="checkbox"/>	
FLAMING CRITERIA (3.2)			
Unsafe escalating combustion (3.2a)	NO	NO	NO
Test assembly consumed (3.2b)	NO	NO	NO
Flaming to extremities and thickness (3.2c) (3.2d)	NO	NO	NO
Flaming continued for more than 120 seconds	NO	NO	NO
Cover split?	NO	NO	NO
TEST RESULT	PASS	PASS	PASS

CONCLUSION:

The sample supplied **meets** the test criteria of BS 7176:2007 + A1:2011 (Low Hazard)

END OF REPORT